


D3B

ROTARY BRUSH CUTTER

- 1 Body frame with double height with internal reinforcements.
- 2 Protection at front and rear by chains.
- 3 Oscillating protection rear cover.
- 4 Adjustable in height rounded skids with "Widest" system.
- 5 Three point linkage made in steel sheet metal with 80 mm off-centre.
- 6 Gearbox input to 540 rpm and 1 3/4" Z20 shaft.
- 7 Chains/blades assembled with pins (rotor RV02).
- 8 Chains/blades assembled with bolts (rotor RV11).
- 9 PTO shaft included with 1 3/8" Z6 tractor side.



MEDIA

MOD.		D3B-160	D3B-180	D3B-200	
TECHNICAL FEATURES					
Working width (m)		1,60	1,80	2,00	
Total width (m)		1,72	1,92	2,12	
Required input power (HP)		70	75	80	
Max. allowed power (HP)		125			
Gearbox input speed (rpm)		540			
Nr. of rotors		1			
Nr. of chains		4			
Nr. of blades		2			
Coupling category		Cat. 2			
Skids		Adjustable in height (3 positions)			
Adjustable height control		Skids			
PTO shaft		PTO shaft with clutch			
Free wheel		Optional			
Weight (kg)		870	990	1.100	
<div><div></div><div>mechanical (mm)</div></div>		720-880	820-980	920-1.080	
REF. MOD.		VM6D16	VM6D18	VM6D20	
OPTIONS					
258	Rotor RV02 assembled with blades				
229	Rotor RV11 assembled with blades				
230	Rotor RV11 assembled with chains				
221	PTO shaft with free wheel incorporated on clutch				
OTHERS					
PTO shaft yoke (tractor side)	T1	T2	T3	T4	T5
	1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

RV02 Standard



RV02 Optional



RV11 Optional



RV11 Optional

