


R3

ROTARY BRUSH CUTTER

- 1 Body with internal reinforcements.
- 2 Replaceable front and rear chain curtains for protection.
- 3 Adjustable in height rounded skids with Widest system.
- 4 Three point linkage made of sheet metal.
- 5 Hydraulic shifting three point linkage with nylon bushes for guiding (shifting models).
- 6 2 rotors with 2 cutting height levels.
- 7 Chains assembled to the rotor with connecting links.
- 8 PTO shaft with clutch.
- 9 Gearbox with 540 rpm input and 1 3/4" Z6.
- 10 ZM patented system and rubber shock-absorbers between gearboxes.
- 11 PTO shaft included with 1 3/8" Z6 tractor side.



MOD.	R3-180	R3-190	R3-200		
TECHNICAL FEATURES					
Working width (m)	1,80	1,90	2,00		
Total width (m)	1,92	2,02	2,12		
Required input power (HP)	70	80	90		
Max. allowed power (HP)	95				
Gearbox input speed (rpm)	540				
Nr. of rotors	2				
Nr. of chains	8				
Coupling category	Cat. 2				
Skids	Adjustable in height (3 positions) with Widest system				
Adjustable height control	Skids				
PTO shaft	PTO shaft with clutch				
Fixed model weight (kg)	912	936	1.096		
Shifting model weight (kg)	982	1.110	1.188		
Hydraulic cylinder stroke (mm)	500				
Working reach 	mechanical (mm)	900-900	950-950	1.000-1.000	
	hydraulic (mm)	1.150-1.150	1.200-1.200	1.250-1.250	
REF. FIXED MODEL	VM4C18	VM4C19	VM4C20		
REF. SHIFTING MODEL	VM5C18	VM5C19	VM5C20		
OPTIONS					
118	Hydraulic rear hood				
019	Mechanical rear pushing frame				
397	Rotor underplate in wear-resistant steel 450				
OTHERS					
PTO shaft yoke (tractor side)	T1	T2	T3	T4	T5
	1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

MULCHERS

BRUSHCUTTERS

VARIOUS

ANNEX

RV07 Standard

