


R4

ROTARY BRUSH CUTTER

- 1 Body with internal reinforcements.
- 2 Front and rear chain curtains for protection.
- 3 Adjustable in height rounded skids with Widest system.
- 4 Three point linkage made of sheet metal with steel tube tensioners.
- 5 Hydraulic shifting three point linkage with nylon bushes for guiding (shifting models).
- 6 2 rotors with 2 cutting height levels.
- 7 Chains assembled to the rotor with pins.
- 8 PTO shaft with clutch.
- 9 Gearbox with 1.000 rpm input and 1 3/4" Z6.
- 10 ZM patented system and rubber shock-absorbers between gearboxes.
- 11 PTO shaft included with 1 3/8" Z6 tractor side.



MOD.		R4-205	R4-220	R4-240	R4-260	
TECHNICAL FEATURES						
Working width (m)		2,05	2,20	2,40	2,60	
Total width (m)		2,17	2,32	2,52	2,72	
Required input power (HP)		85	110	120	140	
Max. allowed power (HP)		110	250			
Gearbox input speed (rpm)		1.000				
Nr. of rotors		2				
Nr. of chains		8				
Coupling category		Cat. 2				
Skids		Adjustable in height (3 positions) with Widest system				
Adjustable height control		Skids				
PTO shaft		PTO shaft with clutch				
Fixed model weight (kg)		1.310	1.430	1.530	1.710	
Shifting model weight (kg)		1.365	1.490	1.705	1.935	
Hydraulic cylinder stroke (mm)		500				
	mechanical (mm)	1.025-1.025	1.100-1.100	1.200-1.200	1.300-1.300	
	hydraulic (mm)	1.275-1.275	1.350-1.350	1.450-1.450	1.550-1.550	
REF. FIXED MODEL		VM6C02	VM6C22	VM6C24	VM6C26	
REF. SHIFTING MODEL		VM7C02	VM7C22	VM7C24	VM7C26	
OPTIONS						
314	Rotor RV07 with connecting links					
397	Rotor underplate in wear-resistant steel 450					
362	Reinforced gearboxes up to 300CV (R5)					
117	Hydraulic rear hood					
095	Mechanical rear pushing frame					
OTHERS						
PTO shaft yoke (tractor side)		T1	T2	T3	T4	T5
		1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

MULCHERS

BRUSHCUTTERS

VARIOUS

ANNEX

RV09 Standard

RV07 Optional

