


R4

ROTARY BRUSH CUTTER

- 1 Body with internal reinforcements.
- 2 Front and rear chain curtains for protection.
- 3 Adjustable in height rounded skids with Widest system.
- 4 Three point linkage made of sheet metal with steel tube tensioners.
- 5 Hydraulic shifting three point linkage with nylon bushes for guiding (shifting models).
- 6 2 rotors with 2 cutting height levels.
- 7 Chains assembled to the rotor with pins.
- 8 PTO shaft with clutch.
- 9 Gearbox with 1.000 rpm input and 1 3/4" Z6.
- 10 ZM patented system and rubber shock-absorbers between gearboxes.
- 11 PTO shaft included with 1 3/8" Z6 tractor side.



MOD.	R4-205	R4-220	R4-240	R4-260	
TECHNICAL FEATURES					
Working width (m)	2,05	2,20	2,40	2,60	
Total width (m)	2,17	2,32	2,52	2,72	
Required input power (HP)	85	110	120	140	
Max. allowed power (HP)	110	250			
Gearbox input speed (rpm)	1.000				
Nr. of rotors	2				
Nr. of chains	8				
Coupling category	Cat. 2				
Skids	Adjustable in height (3 positions) with Widest system				
Adjustable height control	Skids				
PTO shaft	PTO shaft with clutch				
Fixed model weight (kg)	1.310	1.430	1.530	1.710	
Shifting model weight (kg)	1.365	1.490	1.705	1.935	
Hydraulic cylinder stroke (mm)	500				
Working reach 	mechanical (mm)	1.025-1.025	1.100-1.100	1.200-1.200	1.300-1.300
	hydraulic (mm)	1.275-1.275	1.350-1.350	1.450-1.450	1.550-1.550
REF. FIXED MODEL	VM6C02	VM6C22	VM6C24	VM6C26	
REF. SHIFTING MODEL	VM7C02	VM7C22	VM7C24	VM7C26	
OPTIONS					
314	Rotor RV07 with connecting links				
397	Rotor underplate in wear-resistant steel 450				
362	Reinforced gearboxes up to 300CV (R5)				
117	Hydraulic rear hood				
095	Mechanical rear pushing frame				
OTHERS					
PTO shaft yoke (tractor side)	T1	T2	T3	T4	T5
	1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

MULCHERS

BRUSHCUTTERS

VARIOUS

ANNEX

RV09 Standard



RV07 Optional

