

# TFC

## TILLER

- 1 Body built in high strength steel.
- 2 4 chain curtains for front protection.
- 3 Coupling to tractor Cat. 3N.
- 4 Hydraulic rear hood.
- 5 Sidestep system on body sides.
- 6 Skids for protection.
- 7 Inner shell in wear-resistant steel in body.
- 8 Rotor with fixed hammers with helical disposition.
- 9 Transmission with 12 XPC belts and ESB system with automatic tensioner.
- 10 Gearbox with built-in free-wheel, input to 1.000 rpm and 1 3/4" Z6.
- 11 Reinforced PTO shaft.
- 12 Hammers with 3 carbide tips model F13 + F17 (standard).
- 13 PTO shaft included with 1 3/4" Z20 tractor side.



**HARDOX**  
IN MY BODY

**FLEXI**  
STEEL



MOD.		TFC-060			
TECHNICAL FEATURES					
Working width (m)		0,60			
Total width (m)		1,19			
Required input power (HP)		150			
Max. allowed power (HP)		250			
Rotor/s cutting diameter (mm)		905			
Gearbox input speed (rpm)		1.000			
Nr. of hammers	F13 + F17	16 + 6			
	F21 + F17	14 + 6			
Coupling category		Cat. 3N			
Nr. of belts - type		12 XPC			
Skids		Sliding bolted			
Adjustable height control		Roller with hydraulic adjustment (as option)			
Roller diameter / shaft (mm)		510 / 55			
Weight (kg)		2.420			
REF. MOD.		HM2W06			
OPTIONS					
353	Rotor mounted with hammers F21				
125	Rear roller for compacting the soil				
335	Automatic greasing kit				
KM1.F13.2W	Maintenance basic kit (2 hammers F13 + 4 bolts + grease)				
KM2.F13.2W	Maintenance kit (basic kit + 12 belts XPC)				
KM1.F21.2W	Maintenance basic kit (2 hammers F21 + 2 bolts + 2 nuts + grease)				
KM2.F21.2W	Maintenance kit (basic kit + 12 belts XPC)				
OTHERS					
PTO shaft yoke (tractor side)	T1	T2	T3	T4	T5
	1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

MULCHERS

BRUSHCUTTERS

VARIOUS

ANNEX

Hammer F13 Standard



Hammer F17 Standard (sides)



Hammer F21 Optional

