

TFG

MULCHER

- 1 Body built in high strength steel with special design in the front to improve the material entrance.
- 2 4 chain curtains for front protection + 2 extra chain curtains in the middle.
- 3 Coupling to tractor Cat. 3N with fast coupling balls.
- 4 3rd hydraulic point with permanent aligning device (patented). Yoke tractor side Ø32 mm.
- 5 Hydraulic hood with "Superfinish" system.
- 6 Sidestep system on body sides.
- 7 Skids with 2 height positions and side protection.
- 8 Rotor with replaceable shafts, with fixed hammers with helical disposition.
- 9 Hammers with carbide tips and different configurations.
- 10 Transmission with 10 XPC belts and ESB system.
- 11 Gearbox with built-in free-wheel, input to 1.000 rpm and 1 3/4" Z20.
- 12 Reinforced PTO shaft.
- 13 Replaceable counterblades on body frame and on hydraulic hood.
- 14 Hammers with 2 carbide tips TMC Cancela F19 + F20 (standard).
- 15 PTO shaft included with 1 3/4" Z20 tractor side.



MEDIA

MOD.		TFG-225	TFG-250			
TECHNICAL FEATURES						
Working width (m)		2,25	2,50			
Total width (m)		2,74	2,99			
Required input power (HP)		250	275			
Max. allowed power (HP)		360				
Rotor/s cutting diameter (mm)		575,5				
Gearbox input speed (rpm)		1.000				
Nr. of hammers	F19 + F20 / F25 + F20	54 + 2	58 + 2			
	F05 + F13	40 + 2	46 + 2			
	F23	56	60			
Counterblades		1 fixed row + 4 replaceable rows				
Coupling category		Cat. 3N				
Nr. of belts - type		10 XPC				
Skids		Adjustable bolted (2 positions)				
Weight (kg)		3.075	3.215			
REF. MOD.		HMON03	HMON25			
OPTIONS						
345	Rotor mounted with hammers F25					
316	Rotor mounted with hammers F23					
291	Rotor mounted with hammers F05 + F13					
052	Hydraulic rear pushing frame with raker teeth					
335	Automatic greasing kit					
055	Kit turbo PREMIUM					
323	Kit turbo					
057	Skids to work a little bit deeper*					
KM1.F05.0N	Maintenance basic kit (2 hammers F05 + 4 bolts + grease)					
KM2.F05.0N	Maintenance kit (basic kit + 10 belts XPC)					
KM1.F19.0N	Maintenance basic kit (2 hammers F19 + 2 bolts + 2 nuts + grease)					
KM2.F19.0N	Maintenance kit (basic kit + 10 belts XPC)					
KM1.F25.0N	Maintenance basic kit (2 hammers F25 + 2 bolts + 2 nuts + grease)					
KM2.F25.0N	Maintenance kit (basic kit + 10 belts XPC)					
KM1.F23.0N	Maintenance basic kit (2 hammers F23 + 2 bolts + 2 nuts + grease)					
KM2.F23.0N	Maintenance kit (basic kit + 10 belts XPC)					
OTHERS						
PTO shaft yoke (tractor side)		T1	T2	T3	T4	T5
		1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38
3rd point alignment device yoke type (tractor side)	H1	H2	H3	H4	H5	H6
	Ø25	Ø28	Ø32	Ø36	Ø40	Ø45

* This option excludes the Turbo Kit

Hammer F19 Standard Hammer F25 Optional Hammer F20 Standard (sides) Hammer F05 Optional Hammer F13 Optional Hammer F23 Optional



MULCHERS

BRUSHCUTTERS

VARIOUS

ANNEX