

TFZ



MULCHER



BELTS

BELTS



- 1 Body built in high strength steel with special design in the front to improve the material entrance.
- 2 4 chain curtains for front protection + 2 extra chain curtains in the middle.
- 3 Coupling to tractor Cat. 3N with fast coupling balls.
- 4 3rd hydraulic point with permanent aligning device (patented). Yoke tractor side Ø32 mm.
- 5 Hydraulic hood with "Superfinish" system.
- 6 Sidestep system on body sides.
- 7 Skids with 2 height positions and side protection.
- 8 Rotor with replaceable shafts, with fixed hammers with helical disposition.
- 9 Hammers with carbide tips and different configurations.
- 10 Transmission with 10 XPC belts and ESB system.
- 11 Gearbox with built-in free-wheel, input to 1.000 rpm and 1 3/4 Z20.
- 12 Reinforced PTO shaft.
- 13 Replaceable counterblades on body frame and on hydraulic hood.
- 14 Hammers with 2 carbide tips TMC Cancela F19 + F20 (standard).
- 15 PTO shaft included with 1 3/4" Z20 tractor side.



MEDIA



MOD.		TFZ-225	TFZ-250
TECHNICAL FEATURES			
Working width (m)		2,25	2,50
Total width (m)		2,74	2,99
Required input power (HP)		180	200
Max. allowed power (HP)		250	
Rotor/s cutting diameter (mm)		575,5	
Gearbox input speed (rpm)		1.000	
Nr. of hammers	F19 + F20 / F25 + F20	54 + 2	58 + 2
	F05 + F13	40 + 2	46 + 2
	F23	56	60
Counterblades		1 fixed row + 4 replaceable rows	
Coupling category		Cat. 3N	
Nr. of belts - type		10 XPC	
Skids		Bolted adjustable (2 positions)	
Weight (kg)		3.004	3.148
REF. MOD.		HM5U03	HM5U25

OPTIONS	
052	Hydraulic rear pushing frame with raker teeth
055	Kit turbo PREMIUM
323	Kit turbo
057	Skids for deeper work*
316	Rotor assembled with hammers F23
291	Rotor mounted with hammers F05 + F13
335	Automatic greasing kit
345	Rotor assembled with hammers F25
KM1.F05.5U	Maintenance basic kit (2 hammers F05 + 4 bolts + grease)
KM2.F05.5U	Maintenance kit (basic kit + 10 belts XPC)
KM1.F19.5U	Maintenance basic kit (2 hammers F19 + 2 bolts + 2 nuts + grease)
KM2.F19.5U	Maintenance kit (basic kit + 10 belts XPC)
KM1.F25.5U	Maintenance basic kit (2 hammers F25 + 2 bolts + 2 nuts + grease)
KM2.F25.5U	Maintenance kit (basic kit + 10 belts XPC)
KM1.F23.5U	Maintenance basic kit stone (2 hammers F23 + 2 bolts + 2 nuts + grease)
KM2.F23.5U	Maintenance kit stone (basic kit + 10 belts XPC)

	T1	T2	T3	T4	T5
PTO shaft yoke (tractor side)	1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

	H1	H2	H3	H4	H5	H6
3 rd point alignment device yoke type (tractor side)	Ø25	Ø28	Ø32	Ø36	Ø40	Ø45

* This option excludes the Turbo Kit

Hammer F19



Martillo F25



Hammer F20



Hammer F05



Hammer F13



Hammer F23

