




TH

MULCHER

- 1 Body built in high strength steel with sliding three point linkage.
- 2 Protection at front with metallic plates.
- 3 Internal rear roller with adjustment on height for ground adjustment.
- 4 Sidestep system on frame sides.
- 5 Rotor with floating hammers assembled to the rotor with bolts of 20 mm diameter.
- 6 Transmission with 5 belts.
- 7 Gearbox with built-in free wheel and double 1 3/4" Z6 input drive shaft.
- 8 Input to 540 rpm. In option 1.000 rpm by inversion of pulleys (DS system).
- 9 Replaceable counterblades TMC Cancela model C01.
- 10 PTO shaft included with 1 3/8" Z6 tractor side.



MEDIA

MOD.		TH-200D	TH-220D	TH-250D	TH-280D	TH-300D
TECHNICAL FEATURES						
Working width (m)		2,00	2,20	2,50	2,80	3,00
Total width (m)		2,22	2,42	2,77	3,02	3,22
Required input power (HP)		80	90	100	120	150
Max. allowed power (HP)		200				
Rotor/s cutting diameter (mm)		465				
Gearbox input speed (rpm)		540 (1.000 as option)				
Nr. of hammers	A01	32	34	40	44	48
Nr. of blades	A03	96	102	120	132	144
Counterblades		2 replaceable rows				
Coupling category		Cat. 2				
Nr. of belts - type		5 XPB				
Adjustable height control		Rear roller				
Weight (kg)		930	967	1.037	1.099	1.143
Hydraulic cylinder stroke (mm)		500				
 hydraulic (mm)		1.233-1.302	1.233-1.502	1.245-1.810	1.356-1.999	1.518-2.119
REF. MOD.		HM2Y20	HM2Y22	HM2Y25	HM2Y28	HM2Y30
OPTIONS						
035	Rotor assembled with blades A03					
030	Gearbox with double free wheel (reversible connection to tractor)					
091	Removable light panels					
135	Configuration with a gearbox input to 1.000 rpm					
385	Side disc trimmer Ø600 mm (with nylon cord)					
386	Side disc trimmer Ø800 mm (with nylon cord)					
387	Side disc trimmer Ø600 mm (with blades)					
388	Side disc trimmer Ø800 mm (with blades)					
KM1.A01.2Y	Maintenance basic kit (4 hammers A01 + 2 bolts + 2 nuts + grease)					
KM2.A01.2Y	Maintenance kit (basic kit + 5 belts XPB)					
KM1.A03.2Y	Maintenance basic kit (4 sets of blades A03 + 2 bolts + 2 nuts + grease)					
KM2.A03.2Y	Maintenance kit (basic kit + 5 belts XPB)					
OTHERS						
PTO shaft yoke (tractor side)		T1	T2	T3	T4	T5
		1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

Hammer A01 Standard



Blade A03 Optional



Counterblade C01 Standard



Side disc Optional

