


THE

5 - 12 Tn 
MULCHER

- 1 Body built in high strength steel.
 - 2 Double adjustable hood (standard model with 1 hydraulic hood and 2nd hydraulic cylinder for the other hood as an option).
 - 3 Sliding skirts.
 - 4 Rotor with fixed hammers F09 in helical position with "P-CUT" depth limiters.
 - 5 Reversible hammers with carbide.
 - 6 Hydraulic piston motor Bosch Rexroth with adjustable displacement 26-45 cc with built-in anticavitation valve.
 - 7 Replaceable counterblades model C01.
 - 8 Transmission with 4 XPB belts (Poly Chain® GT Carbon optional).
 - 9 Base flange for fastening the optional coupling.
 - 10 Custom coupling to the excavator (optional).
 - 11 Centralized hydraulic outputs and grease points.
- * Hydraulic hoses and connectors to excavator not included.



MOD.		THE-075	THE-100	THE-125
TECHNICAL FEATURES				
Working width [m]		0,75	1,00	1,25
Total width [m]		1,05	1,30	1,55
Required excavator weight Tn (min-max)		5-12		
Required pressure range Bar (min-max)		180-280		
Recommended flow range L/min		60-160	75-160	90-160
Rotor/s cutting diameter (mm)		325		
Nr. of hammers	F09 + F39	18 + 2	24 + 2	30 + 2
	F08 + F38	18 + 2	24 + 2	30 + 2
Counterblades		3 replaceable rows		
Coupling		Bolted flange		
Nr. of belts - type		4 XPB		
Skids		Sliding bolted		
Weight [kg]		455	530	600
REF. MOD.		HH0W07	HH0W10	HH0W01
OPTIONS				
340	Rotor mounted with hammers F08			
081	Custom coupling (depending on the excavator model)			
378	Independent support leg (without coupling) with replaceable tips - Type A			
379	Independent support leg (without coupling) - Type B			
210	Hydraulic motor Bosch Rexroth with adjustable displacement (40-63 cc)			
212	Transmission with Poly Chain® GT Carbon			
348	Protection chains curatins in both hoods			
363	Rotary slew drive for the coupling			
147	Hydraulic cylinder for the second hood			
209	Solenoid valve to switch the main hydraulic flow to the hydraulic hood cylinder			
KM1.F09.0W	Maintenance basic kit (2 hammers F09 + 2 bolts + grease)			
KM2.F09.0W	Maintenance kit (basic kit + 4 belts XPB)			
KM1.F08.0W	Maintenance basic kit (2 hammers F08 + 2 bolts + grease)			
KM2.F08.0W	Maintenance kit (basic kit + 4 belts XPB)			

EXCAVATORS

SKIDSTEER LOADERS

PRIME VEHICLES

ANNEX

