




THQ

2 - 4 Tn 
MULCHER

- 1 Body built in high strength steel.
- 2 Sidestep system on body frame sides.
- 3 Replaceable deflector cover (optional).
- 4 Sliding skids.
- 5 Rotor with fixed hammers F09 in helical position with "P-CUT" depth limiters.
- 6 Reversible hammers with carbide.
- 7 Hydraulic gear motor with 11 cc displacement.
- 8 Replaceable counterblades model C01.
- 9 Base flange for fastening the optional coupling.
- 10 Custom coupling to the excavator (optional).
- * Hydraulic hoses and connectors to excavator not included.



MEDIA

MOD.		THQ-050	THQ-075
TECHNICAL FEATURES			
Working width (m)		0,50	0,75
Total width (m)		0,81	1,06
Required excavator weight Tn (min-max)		2-4	
Required pressure range Bar (min-max)		180-250	
Recommended flow range L/min		35-60	
Rotor/s cutting diameter (mm)		325	
Nr. of hammers	F09 + F39	10 + 2	18 + 2
	F08 + F38	10 + 2	18 + 2
Counterblades		2 replaceable rows	
Coupling		Bolted flange	
Skids		Sliding bolted	
Weight (kg)		185	245
REF. MOD.		HH3G05	HH3G07
OPTIONS			
340	Rotor mounted with hammers F08		
081	Custom coupling (depending on the excavator model)		
143	Hydraulic gear motor 15 cc		
144	Hydraulic gear motor 20 cc		
145	Hydraulic gear motor 25 cc		
338	Compact support leg		
420	Replaceable deflector cover		
363	Rotary slew drive for the coupling		
377	Floating system for the coupling (parallelogram)		
KM1.F09.3G	Maintenance basic kit (2 hammers F09 + 2 bolts + grease)		
KM1.F08.3G	Maintenance basic kit (2 hammers F08 + 2 bolts + grease)		
OTHERS			
E	Packing		
EM	Iron support (pallet)		

Hammer F09 Standard



Hammer F08 Optional



Hammer F39 Standard (sides)



Hammer F38 Optional (sides)



Counterblade C01 Standard



Compact support leg (optional)

