

THS

8 - 15 Tn 
MULCHER

- 1 Body built in high strength steel.
 - 2 Adjustable in height rear roller.
 - 3 Sliding skids.
 - 4 Rotor with floating hammers A01.
 - 5 Hammers assembled to the rotor with $\varnothing 20$ mm bolts.
 - 6 Replaceable counterblades model C01.
 - 7 Sidestep system on body frame sides.
 - 8 Front and rear protection rubber. Front chains protection optional.
 - 9 Base flange for fastening the optional coupling to the excavator.
 - 10 Custom coupling to the excavator (optional).
 - 11 Hydraulic piston motor Bosch-Rexroth with 63 cc fixed displacement with built-in anticavitation valve.
 - 12 Reinforced motor cover.
- * Hydraulic hoses and connectors to excavator not included.



MOD.		THS-100	THS-120	THS-150
TECHNICAL FEATURES				
Working width (m)		1,00	1,20	1,50
Total width (m)		1,35	1,55	1,85
Required excavator weight Tn (min-max)		8-15		
Required pressure range Bar (min-max)		280-380		
Recommended flow range L/min		80-150		
Rotor/s cutting diameter (mm)		465		
Nr. of hammers / blades	A01 / A03	14/42	18/54	24/72
	A18 / A20	10/20	12/24	16/32
Counterblades		2 replaceable rows		
Coupling		Bolted flange		
Skids		Sliding bolted		
Adjustable height control		Roller		
Weight (kg)		435	480	545
REF. MOD.		HH6X10	HH6X12	HH6X15
OPTIONS				
035	Rotor assembled with blades A03			
319	Rotor assembled with hammers A18			
320	Rotor assembled with blades A20			
203	Custom coupling (depending on the excavator model)			
333	Protection at front with chains			
363	Rotary slew drive for the coupling			
377	Floating system for the coupling (parallelogram)			
KM1.A01.6X	Maintenance basic kit (4 hammers A01 + 2 bolts + 2 nuts + grease)			
KM1.A03.6X	Maintenance kit (4 sets of blades A03 + 2 bolts + 2 nuts + grease)			
KM1.A18.6X	Maintenance basic kit (2 hammers A18 + 1 bolt + 1 nut + grease)			
KM1.A20.6X	Maintenance kit (2 sets of blades A20 + 1 bolt + 1 nut + grease)			

EXCAVATORS

SKIDSTEER LOADERS

PRIME VEHICLES

ANNEX

Hammer A01 Standard



Blade A03 Optional



Hammer A18 Optional



Blade A20 Optional



Counterblade C01 Standard

