

# TJA

## MULCHER


- 1 Body built in high strength steel with fixed three point linkage.
- 2 Sliding bolted side skids with large soles surface.
- 3 Protection by metallic plates at front or chain curtains (in option).
- 4 Rotor with floating hammers A10 assembled with bolt with 24 mm diameter (optional A07 blades).
- 5 Transmission by 5 belts and automatic tensioner.
- 6 Input to 540 rpm.
- 7 Gearbox with built-in free wheel and 1 3/4" Z6 input shaft.
- 8 Replaceable counterblades TMC Cancela model C01.
- 9 PTO shaft included with 1 3/8" Z6 tractor side.



**FLEXI<sup>®</sup>**  
**STEEL**



MEDIA

MOD.			TJA-150	TJA-180	TJA-200	
TECHNICAL FEATURES						
Working width (m)			1,50	1,80	2,00	
Total width (m)			1,80	2,10	2,30	
Required input power (HP)			60	70	80	
Max. allowed power (HP)			150			
Rotor/s cutting diameter (mm)			660			
Gearbox input speed (rpm)			540			
Nr. of hammers	A10		18	22	26	
Nr. of blades	A07		54	66	78	
Counterblades			2 replaceable rows			
Coupling category			Cat. 2			
Nr. of belts - type			5 XPB			
Skids			Adjustable bolted (2 positions)			
Adjustable height control			Skids (2 positions)			
Weight (kg)			760	820	870	
Working reach 		mechanical 1 (mm)	750-750	900-900	1.000-1.000	
REF. MOD.			HM7L15	HM7L18	HM7L20	
OPTIONS						
153	Rotor assembled with blades A07					
274	Protection at front with chains					
KM1.A10.7L	Maintenance basic kit (4 hammers A10 + 2 bolts + 2 nuts + grease)					
KM2.A10.7L	Maintenance kit (basic kit + 5 belts XPB)					
KM1.A07.7L	Maintenance basic kit (4 sets of blades A07 + 2 bolts + 2 nuts + grease)					
KM2.A07.7L	Maintenance kit (basic kit + 5 belts XPB)					
OTHERS						
PTO shaft yoke (tractor side)		T1	T2	T3	T4	T5
		1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

Hammer A10 Standard



Blade A07 Optional



Counterblade C01 Standard

