

TJB

MULCHER


- 1 Body built in high strength steel.
- 2 Rear hood with double mechanical adjustment for checking and replacing the cutting tools.
- 3 External rear roller with adjustment on height (wheels as option).
- 4 Protection by metallic plates at front or chain curtains (in option).
- 5 Hydraulic shifting three point linkage (shifting model).
- 6 Rotor with floating hammers A10 assembled with bolt with 24 mm diameter (optional A07 blades).
- 7 Transmission by 5 belts and automatic tensioner.
- 8 Input to 540 rpm.
- 9 Gearbox with built-in free wheel and 1 3/4" Z6 input shaft.
- 10 Replaceable counterblades TMC Cancela model C01.
- 11 PTO shaft included with 1 3/8" Z6 tractor side.



**FLEXI
STEEL**



MEDIA

MOD.		TJB-200	TJB-250	TJB-280	TJB-300	
TECHNICAL FEATURES						
Working width (m)		2,00	2,50	2,80	3,00	
Total width (m)		2,28	2,78	3,08	3,28	
Required input power (HP)		70	80	100	120	
Max. allowed power (HP)		150				
Rotor/s cutting diameter (mm)		660				
Gearbox input speed (rpm)		540				
Nr. of hammers	A10	26	32	36	38	
Nr. of blades	A07	78	96	108	114	
Counterblades		2 replaceable rows				
Coupling category		Cat. 2				
Nr. of belts - type		5 XPB				
Skids		Adjustable bolted (2 positions)				
Adjustable height control		Roller (4 positions) / Skids (2 positions) / Wheels (4 positions)				
Fixed model weight (kg)		1.035	1.230	1.305	1.375	
Shifting model weight (kg)		1.135	1.330	1.405	1.475	
Hydraulic cylinder stroke (mm)		500				
Working reach 	mechanical 1 (mm)	1.000-1.000	1.250-1.250	1.400-1.400	1.500-1.500	
	hydraulic (mm)	1.268-1.268	1.268-1.768	1.418-1.918	1.517-2.017	
REF. FIXED MODEL		HMOR20	HMOR25	HMOR28	HMOR30	
REF. SHIFTING MODEL		HM6L20	HM6L25	HM6L28	HM6L30	
OPTIONS						
153	Rotor assembled with blades A07					
037	Assembled with rear wheels without roller (10.0/80-12")					
274	Protection at front with chains					
233	Roller scraper					
091	Removable light panels					
092	Hydraulic rear hood (for maintenance purposes)					
240	Fins on rear hood for spreading (Not available for Italy and other countries according to country specific regulations)					
KM1.A10.0R	Maintenance basic kit (4 hammers A10 + 2 bolts + 2 nuts + grease)					
KM2.A10.0R	Maintenance kit (basic kit + 5 belts XPB)					
KM1.A07.0R	Maintenance basic kit (4 sets of blades A07 + 2 bolts + 2 nuts + grease)					
KM2.A07.0R	Maintenance kit (basic kit + 5 belts XPB)					
OTHERS						
PTO shaft yoke (tractor side)		T1	T2	T3	T4	T5
		1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

Hammer A10 Standard



Blade A07 Optional



Counterblade C01 Standard

