
TLJ

MULCHER

1 Body built in high strength steel.
2 Hydraulic hood.
3 Sliding skids.
4 Rotor with replaceable shafts and fixed hammers F49 with helical arrangement and "P-CUT" depth limiters.
5 Reversible hammers TMC Cancela F49.
6 Adjustable motor 40-63 cc displacement engine.
7 Replaceable counterblades model C01.
8 Transmission with 4 XPB belts.
9 Base flange for coupling to the remote controlled carrier included.
10 Mechanical pushing frame with raker teeth.
* Hydraulic hoses and connectors to remote controlled carrier not included.







HARDOX IN MY BODY · FLEXI STEEL · P-CUT P-CUT · ESB · SIDESTEP · ALE · HDX · Ø 200 mm · x4 BELTS



MEDIA

TMC CANCELA

MOD.		TLJ-150
TECHNICAL FEATURES		
Working width (m)		1,50
Total width (m)		1,85
Required pressure range Bar (min-max)		200-380
Recommended flow range L/min		75-160
Rotor/s cutting diameter (mm)		380
Nr. of hammers	F49 + F38 / F09 + F38 / F08 + F38	36 + 2
Counterblades		3 replaceable rows
Coupling		Bolted flange
Nr. of belts - type		4 XPB
Skids		Sliding bolted (2 positions)
Weight (kg)		753
REF. MOD. RIGHT		**HH6G15**
REF. MOD. LEFT		**HH7G15**
OPTIONS		
401	Rotor mounted with hammers F09	*[+0 kg]*
340	Rotor mounted with hammers F08	*[+0 kg]*
326	Rubber protection	*[+6 kg]*
407	Hydraulic piston motor with fixed displacement 45 cc (with built-in flush valve)	*[+0 kg]*
104	Hydraulic piston motor with fixed displacement 63 cc	*[+0 kg]*
327	Hydraulic pushing frame	*[+10 kg]*
209	Solenoid diverter valve to switch the main flow to the hydraulic hood	*[+10 kg]*
430	Universal coupling plate for skid steer loaders	*[+80 kg]*
382	Flushing valve	*[+7 kg]*
KM1.F49.6G	Maintenance basic kit (2 hammers F49 + 2 bolts + grease)	
KM2.F49.6G	Maintenance kit (basic kit + 4 belts XPB)	
KM1.F09.6G	Maintenance basic kit (2 hammers F09 + 2 bolts + grease)	
KM2.F09.6G	Maintenance kit (basic kit + 4 belts XPB)	
KM1.F08.6G	Maintenance basic kit (2 hammers F08 + 2 bolts + grease)	
KM2.F08.6G	Maintenance kit (basic kit + 4 belts XPB)	

Hammer F49 Standard



Hammer F09 Optional



Hammer F08 Optional



Hammer F38 Standard (sides)



Counterblade C01 Standard

