



TLP



MULCHER

- 1 Body built in high strength steel.
 - 2 Protection at front by metallic plates.
 - 3 Sliding skids.
 - 4 External rear roller for a better adjustment to the field.
 - 5 Rotor with floating hammers assembled with bolts of 20 mm diameter.
 - 6 Hydraulic piston motor Bosch Rexroth with fixed displacement 28 cc with built-in anticavitation valve.
 - 7 Replaceable counterblades model C01.
 - 8 Transmission with 4 XPB belts.
 - 9 Sidestep system on body frame sides.
 - 10 Base flange for coupling to the remote controlled carrier including.
- * Hydraulic hoses and connectors to remote controlled carrier not included.



**FLEXI
STEEL**



MEDIA

MOD.		TLP-120	TLP-140
TECHNICAL FEATURES			
Working width (m)		1,20	1,40
Total width (m)		1,42	1,62
Required pressure range Bar (min-max)		200-280 / 380**	
Recommended flow range L/min		60 - 120	70 - 120
Rotor/s cutting diameter (mm)		385	
Nr. of blades	A01	18	22
	A02	10	12
Nr. of hammers	A03	54	66
Counterblades		2 replaceable rows	
Coupling		Bolted flange	
Nr. of belts - type		4 XPB	
Skids		Sliding bolted	
Adjustable height control		Rear roller	
Weight (kg)		435	490
REF. MOD.		HHOJ12	HHOJ14
OPTIONS			
035	Rotor assembled with blades A03		
396	Rotor assembled with hammers A02		
326	Rubber protection		
350	Hydraulic piston motor with fixed displacement 32 cc		
211	Hydraulic piston motor with 26-45 cc adjustable displacement		
382	Flushing valve		
259	Protection at front with chains		
233	Roller scraper		
334	Replaceable internal frame in high strength steel		
KM1.A01.OJ	Maintenance basic kit (4 hammers A01 + 2 bolts + grease)		
KM2.A01.OJ	Maintenance kit (basic kit + 4 belts XPB)		
KM1.A02.OJ	Maintenance basic kit (2 hammers A02 + 1 bolt + 1 nut + grease)		
KM2.A02.OJ	Maintenance kit (basic kit + 4 belts XPB)		
KM1.A03.OJ	Maintenance basic kit stone (4 sets of blades A03 + 2 bolts + grease)		
KM2.A03.OJ	Maintenance kit (basic kit + 4 belts XPB)		

** Maximum pressure for 28 cc and 32 cc fixed displacement motors

Hammer A01 Standard



Hammer A02 Optional



Blade A03 Optional



Counterblade C01 Standard

