TOS



MULCHER

















DELTC





- 1 Body built in high strength steel.
- 2 Fixed bolted three point linkage. Adjustable to work on reverse position.
- 3 Hydraulic double pick-up feeder with speed adjustment.
- 4 Rear fixed wheels (18/7-8") with height adjustment.
- 5 Gearbox with built-in free wheel with 1"3/4 Z6 input shaft.
- 6 Mulching system with an open chamber (direct to the ground).
- 7 Rotor with fixed hammers with patented mulching system.
- 8 Transmission with 6 belts and automatic tensioner.
- 9 Pick-up hydraulic motor with a side extension shaft with bearings.
- 10 Input to 1.000 rpm. As option 540 rpm by inversion of pulleys (DS system).
- 11 Replaceable counterblades made in wear resistant steel.
- 12 PTO shaft included with 1 3/8" Z6 tractor side.





MOD.					TOS-150	TOS-180	TOS-210
TECHNICA	L FEATURES						
Working width (m)					1,50	1,80	2,10
Total width (m)					1,95	2,25	2,55
Required input power (HP)					110	130	150
Max. allowed power (HP)					200		
Rotor/s cutting diameter (mm)					545		
Gearbox input speed (rpm)					1.000 (540 as option)		
Nr. of hammers A06					20 + 20	22 + 22	26 + 26
Counterblades Counterblades					2 replaceable rows + 1 fixed row		
Coupling category Nr. of belts - type					Cat. 2 6 XPB		
Adjustable height control				Wheels			
Weight (kg)				1.330	1.420	1.696	
Working reach mechanical 1 (mm)					750-750	900-900	1.050-1.05
OPTIONS							
318	Side skirts						
044	Assembled with rear 360° swinging wheels (18/7-8")						
134	Configuration with a gearbox input of 540 rpm						
136	Tines for rake						
	Double kit of tines for the rake						
137	Double kit of tines for the rake						
137 285							
	Solid tyres (18/7-8")	double free wheel g	earbox)				
285		double free wheel go	earbox)				
285 286 304	Solid tyres (18/7-8") Progessive gearbox starter (not available with Second three point linkage		earbox)				
285 286	Solid tyres (18/7-8") Progessive gearbox starter (not available with Second three point linkage Maintenance basic kit (2 sets of hammers A06		earbox)				
285 286 304 KM1.A06.8Y	Solid tyres (18/7-8") Progessive gearbox starter (not available with Second three point linkage Maintenance basic kit (2 sets of hammers A06		earbox)				
285 286 304 KM1.A06.8Y KM2.A06.8Y	Solid tyres (18/7-8") Progessive gearbox starter (not available with Second three point linkage Maintenance basic kit (2 sets of hammers A06		earbox)	Т3	T4		T5

Hammer A06

