

TOX


MULCHER

- 1 Body built in high strength steel.
- 2 Fixed bolted three point linkage.
- 3 Rubber protection at rear.
- 4 Hydraulic double reinforced pick-up feeder with independent speed adjustment.
- 5 Entry size adjustable (adjustable top feeder by hydraulic cylinders).
- 6 Rear fixed wheels with height adjustment.
- 7 Gearbox with built-in free wheel with 1 3/4" Z6 input shaft.
- 8 Mulching system with an open chamber (direct to the ground).
- 9 Rotor with fixed hammers with patented mulching system.
- 10 Transmission with 6 belts and automatic tensioner.
- 11 Pick-up hydraulic motor with a side extension shaft with bearings.
- 12 Replaceable counterblades made in wear resistant steel.
- 13 Input to 1.000 rpm. As option 540 rpm by inversion of pulleys (DS system).
- 14 PTO shaft included with 1 3/8" Z6 tractor side.



Compatible with CHR (page 110)



MOD.		TOX-180	TOX-210	
TECHNICAL FEATURES				
Working width (m)		1,80	2,10	
Total width (m)		2,25	2,55	
Required input power (HP)		130	140	
Max. allowed power (HP)		200		
Rotor/s cutting diameter (mm)		545		
Gearbox input speed (rpm)		1.000 (540 as option)		
Nr. of hammers	A06	22 + 22	26 + 26	
Counterblades		2 replaceable rows + 1 fixed row		
Coupling category		Cat. 2		
Nr. of belts - type		6 XPB		
Adjustable height control		Wheels		
Weight (kg)		1.740	1.885	
Working reach	 mechanical 1 (mm)	917,5-917,5	1.017,5-1.017,5	
REF. MOD.		HM8K18	HM8K21	
OPTIONS				
134	Configuration with a gearbox input of 540 rpm			
136	Tines for rake			
137	Double kit of tines for the rake			
285	Solid tyres (18/7-8")			
028	Gearbox with double free wheel (to work on the front linkage of the tractor)			
286	Progressive gearbox starter			
427	Conversion from mechanically to hydraulically driven machine with standard three-point hitch for tractor			
430	Universal coupling plate for skid steer loaders			
KM1.A06.8K	Maintenance basic kit (2 sets of hammers A06 + 2 bolts + grease)			
KM2.A06.8K	Maintenance kit (basic kit + 6 belts XPB)			
OTHERS				
PTO shaft yoke (tractor side)	T1	T2	T3	T4
	1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20

Hammer A06 Standard



Transformation Optional

