## **TPH**

## **MULCHER**

- 1 Body built in high strength steel and bolted three point linkage with multiple positions.
- 2 Protection at front with chains.
- 3 Sliding skids.
- 4 Hydraulic rear hood with incorporated external roller.
- 5 Hydraulic three point linkage (shifting model) with the possibility to be assembled on the same body of the fixed model.
- 6 Rotor with floating hammers assembled to the rotor with bolts of 20 mm diameter.
- 7 Transmission with 4 belts.
- 8 Gearbox with built-in free wheel with 1 3/8" Z6 input shaft to 540 rpm.
- 9 Replaceable counterblades C01.
- 10 Replaceable counterblades TMC Cancela model C01.
- 11 PTO shaft included with 1 3/8" Z6 tractor side.

















MEDIA



MOD.						TPH-120	TPH-140	TPH-160
TECHNICAL FEA	ATURES							
Working width (m)						1,20	1,40	1,60
Total width (m)						1,42	1,62	1,82
Required input power (HP)						50	55	60
Max. allowed power (HP)						70		
Rotor/s cutting diameter (mm)						385		
Gearbox input speed (rpm)						540		
Vr. of hamm	A01						22	26
11. 01 11011111	A02						12	14
Nr. of blades A03						54	66	78
Counterblades					2 replaceable rows			
Coupling category					Cat. 1 / Cat. 2			
Nr. of belts - type					4 XPB			
Skids					Adjustable bolted (2 positions)			
Adjustable height control  Weight (kg)					473	Rear roller 516	557	
Shifting model weight (kg)						531	580	627
Hydraulic cylinder stroke (mm)						340	340	400
mechanical (mm)						600-600	700-700	800-800
Working rea	nch 📲	hydraulic (mm)				805-770	795-980	905-1.130
REF. MOD.					HM3M12	HM3M14	HM3M16	
REF. SHIFTING MODEL						HM9L12	HM9L14	HM9L16
OPTIONS								
035	Rotor assembled with blades A03							
396	Rotor mounted with hammers A02							
332	Protection with chains at front							
	Maintenance basic kit [4 hammers A01 + 2 bolts + 2 nuts + grease]							
	Maintenance kit (basic kit + 4 belts XPB)							
	Maintenance basic kit (2 hammers A02 + 1 bolt + 1 nut + grease)							
	Maintenance kit (basic kit + 4 belts XPB)							
KM2.A03.3M Maintenance basic kit (4 sets of blades A03 + 2 botts + 2 nuts + grease)								
	Maintenance Kit	(Dasic KIT + 4 Delts APB)						
OTHERS								
PTO shaft yoke (tractor side)		T1	T2	Т3	T4		T5	
		1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z	'20 [	D8x32x38	

Hammer A01 Standard

Hammer A02 Optional

Blade A03 Optional

Counterblade C01 Standard







