TS

MULCHER

- 1 Three point linkage with double arm built in high strength steel with Cat. 3 coupling.
- Security collision system built-in each arm with a mechanical adjustment.
- 3 Flotation system on each arm to control the pressure of the machine on the ground.
- 4 Partial lifting system with an automatic adjustment of the mulcher heads during turns and changes of position at work.
- 5 Double pivot point on the arms and on the mulcher heads to guarantee an excellent adjustment to the ground.
- 6 Light panels.
- Mechanical safety device for transport and stabilization jacks for storing.

- 8 Mulching heads with the bodies built in high strength steel.
- Protection at front with metallic plates.
- 10 Rear roller with height adjustment.
- 11 Mulching heads sides with "Sidestep" system.
- **12** Rotor with floating hammers fixed to the rotor with a 20 mm diameter bolt.
- 13 Transmission with 6 + 6 belts and automatic tensioners.
- 14 Gearbox with 1 3/4" Z6 input shaft.
- **15** Input to 1.000 rpm.
- 16 Replaceable counter-blades TMC Cancela model C01.
- 17 PTO shaft included with 1 3/8" Z6 tractor side.

















MOD.						TS-76	TS-840	
TECHNICAL FEA	ATURES							
Working width (m)						7,60	8,40	
Total width (m)						8,03	8,50	
Required input power (HP)						180	200	
Max. allowed power (HP)							365	
Rotor/s cutting diameter (mm)							463,1	
Gearbox input speed (rpm)							1.000	
Nr. of hammers A01				88	96			
Nr. of blades A03						264	288	
Counterblades						1 rep	1 fixed row + 1 replaceable row (in each mulcher head)	
Coupling category							Cat. 3	
Nr. of belts - type						6	6 + 6 XPB	
Adjustable height control							Roller	
Weight (kg)						2.462	2.762	
Transport width (m)							3,20	
Working reach mechanical 1 (mm)					3.800-3.8	4.200-4.200		
REF. MOD. OPTIONS						HM6R76	HM6R84	
035	Rotor assembled with blades A03							
KM1.A01.6R	Maintenance basic kit [4 hammers A01 + 2 bolts + 2 nuts + grease]							
KM2.A01.6R	Maintenance kit (basic kit + 12 belts XPB)							
KM1.A03.6R	Maintenance basic kit (4 sets of blades A03 + 2 bolts + 2 nuts + grease)							
KM2.A03.6R	M2.A03.6R Maintenance kit (basic kit + 12 belts XPB)							
OTHERS								
PTO shaft yoke (tractor side)		T1	T2	Т3	Т4	T5		
		1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38		

