## **TSL**

## **MULCHER**

- 1 Three point linkage built in high strength steel with Cat. 3 linkage.
- 2 Security collision system built-in each arm with mechanical adjustment.
- 3 Flotation system on each the arm to control the pressure of the machine on the ground.
- 4 Partial lifting system with an automatic adjustment of the mulcher head during turns and changes of position at work.
- 5 Double pivot point on the arm and on the mulcher head to guarantee an excellent adjustment to the ground.
- 6 Mechanical safety device for transport and stabilization jacks for storing.

- 7 Mulching head with the body built in high strength steel.
- 8 Protection at front with metallic plates.
- 9 Rear roller with height adjustment.
- 10 Mulching head side with "Sidestep" system.
- 11 Rotor with floating hammers fixed to the rotor with a 20 mm diameter bolt.
- 12 Transmission with 6 belts and automatic tensioner.
- 13 Gearbox with 1 3/4" Z6 input shaft.
- 14 Input to 540 rpm. In option 1.000 rpm.
- 15 Replaceable counter-blades TMC Cancela model C01.
- 16 PTO shaft included with 1 3/8" Z6 tractor side.







MOD.								TSL-300
TECHNICAL FEA	TURES							
Working width (m)								3,00
Total width (m)								3,25
Required input power (HP)								150
Max. allowed power (HP)								365
Rotor/s cutting diameter (mm)								463,1
Gearbox input speed (rpm)								540 (1.000
								as option)
Nr. of hammers A01 Nr. of blades A03								48 144
NI. UI Didues Aub								1 fixed
Counterblades								row + 1 replaceable row
Coupling category								Cat. 3
Nr. of belts - type								6 XPB
Adjustable height control								Roller
Weight (kg)								1.450
Transport width (m)								2,40
Working rea	ch		mechanical 1 (mm)					4.200-4.200
REF. MOD.								HM7N30
OPTIONS								
035	Rotor assembled with blades A03							
135	Configuration with a gearbox input to 1.000 rpm							
KM1.A01.7N	Maintenance basic kit (4 hammers A01 + 2 bolts + 2 nuts + grease)							
KM2.A01.7N	Maintenance kit (basic kit + 6 belts XPB)							
KM1.A03.7N	N Maintenance basic kit (4 sets of blades A03 + 2 bolts + 2 nuts + grease)							
	N Maintenance kit (basic kit + 6 belts XPB)							
OTHERS								
PTO shaft yoke (tractor side)			T1	T2	тз	Т4	Т5	
				1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

Hammer A01 Standard

Blade A03 Optional

Counterblade C01 Standard





