P patented | 70% saving | 3X faster

TVC

MULCHER

1 Body built in high strength steel.
2 Fixed bolted three point linkage. Adjustable to work on reverse position.
3 Hydraulic double pick-up feeder with speed adjustment.
4 Rear fixed wheels or optional swinging wheels 360º (18/7-8") with height adjustment.
5 Mulching system with an open chamber (direct to the ground).
6 Rotor with fixed hammers with patented mulching system.
7 Transmission with 5 belts.
8 Gearbox with built-in free wheel with 1 3/4" Z6 input shaft.
9 Input to 540 rpm. As option 1.000 rpm by inversion of pulleys (DS system).
10 Replaceable counterblades made in wear resistant steel.
11 Pick-up hydraulic motor with a side extension shaft with bearings.
12 PTO shaft included with 1 3/8" Z6 tractor side.



Compatible with CH (p. 96)

REVERSIBLE MODEL | HARDOX IN MY BODY | FLEXI STEEL | ESB | ALE | HDX | DS | 360º | Ø 150 mm | x5 BELTS



TMC CANCELA

MOD.		TVC-150	TVC-180	TVC-200
TECHNICAL FEATURES				
Working width (m)		1,50	1,80	2,00
Total width (m)		1,93	2,23	2,43
Required input power (HP)		80	90	100
Max. allowed power (HP)		120		
Rotor/s cutting diameter (mm)		465		
Gearbox input speed (rpm)		540 (1.000 as option)		
Nr. of hammers	A06	20 + 20	22 + 22	26 + 26
Counterblades		2 replaceable rows + 1 fixed row		
Coupling category		Cat. 2		
Nr. of belts - type		5 XPB		
Adjustable height control		Roller / Wheels		
Weight (kg)		1.130	1.275	1.360
Working reach 	mechanical 1 (mm)	767,5-767,5	917,5-917,5	1.017,5-1.017,5
REF. MOD.		**HM9S15**	**HM9S18**	**HM9S20**

OPTIONS	
249	Side skirts TVC
394	Sideskirts with spikes for stony soil
028	Gearbox with a double free wheel (to work on reverse position)
136	Tines for rake
137	Double kit of tines for the rake
038	Adjustable on height rear roller without wheels
304	Second three point linkage
135	Configuration with a gearbox input to 1.000 rpm
286	Progessive gearbox starter (not available with double freewheel gearbox)
044	Assembled with rear 360º swinging wheels (18/7-8")
427	Conversion from mechanically to hydraulically driven machine with standard three-point hitch for tractor
430	Universal coupling plate for skid steer loaders
KM1.A06.9S	Maintenance basic kit (2 sets of hammers A06 + 2 bolts + grease)
KM2.A06.9S	Maintenance kit (basic kit + 5 belts XPB)

OTHERS				
PTO shaft yoke (tractor side)	**T1**	**T2**	**T3**	**T4**
	1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20

Hammer A06 Standard



Transformation Optional

