P patented | 70% saving | 3X faster

TVL

MULCHER

1 Body built in high strength steel.
2 Hydraulic double pick-up feeder with speed adjustment.
3 Rear fixed wheels (18/7-8") with height adjustment.
4 Mulching system with an open chamber and rear screener.
5 Rotor with fixed hammers with patented mulching system.
6 Transmission with 5 belts.
7 Gearbox with built-in free wheel 1 3/8" Z6 input shaft.
8 Input to 540 rpm. In option 1.000 rpm by inversion of pulleys (DS system).
9 Replaceable special counterblades made in wear resistant steel.
10 Pick-up hydraulic motor with a side extension shaft with bearings.
11 PTO shaft included with 1 3/8" Z6 tractor side.



FORWARD DIRECTION



HARDOX® IN MY BODY | FLEXI STEEL® | ESB | ALE | HDX | DS | Ø 125 mm | x5 BELTS



MEDIA

TMC CANCELA

MOD.		TVL-150	TVL-180	TVL-200
TECHNICAL FEATURES				
Working width (m)		1,50	1,80	2,00
Total width (m)		1,76	2,06	2,26
Required input power (HP)		80	90	100
Max. allowed power (HP)		100		
Rotor/s cutting diameter (mm)		415		
Gearbox input speed (rpm)		540 (1.000 as option)		
Nr. of hammers	A06	20 + 20	22 + 22	26 + 26
Counterblades		2 replaceable rows		
Coupling category		Cat. 2		
Nr. of belts - type		5 XPB		
Adjustable height control		Roller / Wheels		
Weight (kg)		1.055	1.190	1.305
Working reach 	mechanical 1 (mm)	767,5-767,5	917,5-917,5	1.017,5-1.017,5
REF. MOD.		**HM0G15**	**HM0G18**	**HM0G20**

OPTIONS

249	Side skirt
394	Sideskirts with spikes for stony soil
136	Tines for rake
137	Double kit of tines for the rake
028	Double kit of tines for the rake
038	Adjustable on height rear roller without wheels
135	Configuration with a gearbox input to 1.000 rpm
KM1.A06.0G	Maintenance basic kit (2 sets of hammers A06 + 2 bolts + grease)
KM2.A06.0G	Maintenance kit (basic kit + 5 belts XPB)

OTHERS

PTO shaft yoke (tractor side)	T1	T2	T3	T4
	1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20

Hammer A06 Standard

