

# TWF



## MULCHER

- 1 Body built in high strength steel.
  - 2 Sidestep system on body frame sides.
  - 3 4 chain curtains for front protection.
  - 4 Hydraulic hood for improving the material entrance and with replaceable counterblades.
  - 5 Adjustable in height sliding skids with 3 positions.
  - 6 Mechanical pushing frame. Hydraulic pushing frame as option.
  - 7 Rotor with fixed hammers with helical disposition.
  - 8 Hammers with 2 carbide tips F19 + F20.
  - 9 Transmission with 6 XPB belts (Poly Chain GT Carbon as option).
  - 10 Side extension device between motor and pulleys with ESB system.
  - 11 Hydraulic piston motor Bosch Rexroth with fixed displacement 63 cc and with built-in anticavitation valve.
  - 12 Centralized hydraulic connections, greasing points and visible pressure gauge.
  - 13 Universal coupling plate for skid steer loaders.
- \* Hydraulic hoses and connectors to skid steer loader not included.



MOD.		TWF-150	TWF-180
<b>TECHNICAL FEATURES</b>			
Working width (m)		1,50	1,80
Total width (m)		1,87	2,17
Required pressure range Bar (min-max)		220-380	
Recommended flow range L/min		150-200	180-200
Rotor/s cutting diameter (mm)		415	
Nr. of hammers	F19 + F20 / F25 + F20	34 + 2	42 + 2
Counterblades		4 replaceable rows	
Coupling		Universal coupling plate	
Nr. of belts - type		6 XPB	
Skids		Bolted adjustable (3 positions)	
Weight (kg)		1.178	1.268
REF. MOD.		HH6W15	HH6W18
<b>OPTIONS</b>			
345	Rotor mounted with hammers F25		
105	Hydraulic piston motor with fixed displacement 80 cc		
357	Hydraulic piston motor with variable displacement up to 85 cc		
079	**Hydraulic piston motor with variable displacement up to 115 cc		
327	Hydraulic pushing frame		
209	Solenoid diverter valve to switch the main flow to the hydraulic hood		
212	Transmission with Poly Chain® GT Carbon		
358	"P-CUT" depth bite limiters (Performance Cut)		
KM1.F19.6W	Maintenance basic kit (2 hammers F19 + 2 bolts + grease)		
KM2.F19.6W	Maintenance kit (basic kit + 6 belts XPB)		
KM1.F25.6W	Maintenance basic kit (2 hammers F25 + 2 bolts + grease)		
KM2.F25.6W	Maintenance kit (basic kit + 6 belts XPB)		

\*\* Optional only available including the option transmission with Poly Chain GT Carbon

Hammer F19 Standard



Hammer F25 Optional



Hammer F20 Standard (sides)

