

# TWJ



- 1 Body built in high strength steel.
  - 2 Sidestep system on body frame sides.
  - 3 2 chain curtains for front protection.
  - 4 Hydraulic hood for improving the material entrance and with replaceable counterblades.
  - 5 Adjustable in height sliding skids with 2 positions.
  - 6 Mechanical pushing frame.
  - 7 Rotor with fixed hammers with helical disposition.
  - 8 Hammers with 2 carbide tips F08.
  - 9 Transmission with 4 XPB belts.
  - 10 Side extension device between motor and pulleys with ESB system.
  - 11 Hydraulic piston motor Bosch Rexroth with adjustable displacement 40/63 cc and with built-in anticavitation valve.
  - 12 Universal coupling plate for skid steer loaders.
- \* Hydraulic hoses and connectors to skid steer loader not included.



MEDIA

MOD.		TWJ-150	TWJ-180
<b>TECHNICAL FEATURES</b>			
Working width (m)		1,50	1,80
Total width (m)		1,78	2,08
Required pressure range Bar (min-max)		180-280	
Recommended flow range L/min		85-175	
Rotor/s cutting diameter (mm)		380	
Nr. of hammers	F08 / F09	38	46
Counterblades		3 replaceable rows + 1 adjustable	
Coupling		Universal coupling plate	
Nr. of belts - type		4 XPB	
Skids		Bolted adjustable (2 positions)	
Weight (kg)		955	1.045
<b>REF. MOD.</b>		<b>HH4J15</b>	<b>HH4J18</b>
<b>OPTIONS</b>			
401	Rotor mounted with hammers F09		
209	Solenoid diverter valve to switch the main flow to the hydraulic hood		
358	"P-CUT" depth bite limiters (Performance Cut)		
KM1.F08.4J	Maintenance basic kit (2 hammers F08 + 2 bolts + grease)		
KM2.F08.4J	Maintenance kit (basic kit + 4 belts XPB)		
KM1.F09.4J	Maintenance basic kit (2 hammers F09 + 2 bolts + grease)		
KM2.F09.4J	Maintenance kit (basic kit + 4 belts XPB)		
<b>OTHERS</b>			
E	Packing		
EM	Iron support (pallet)		

Hammer F08 Standard



Hammer F09 Optional

Counterblade C01  
Standard