


TWX



MULCHER

- 1 Body built in high strength steel.
 - 2 2 chain curtains for front protection.
 - 3 Adjustable in height skids with 3 positions and with deflectors to help the material to enter the chamber.
 - 4 Internal modular replaceable shell in wear resistant steel.
 - 5 Adjustable input counterblade.
 - 6 Rotor with fixed hammers with helical disposition.
 - 7 Hammers with 2 carbide tips F29 + side scrapers F37.
 - 8 Transmission with belt Poly Chain® GT Carbon.
 - 9 Side extension device between motor and pulleys with ESB system.
 - 10 Hydraulic piston motor Bosch Rexroth with fixed displacement 125 cc.
 - 11 Centralized hydraulic connections, greasing points and visible pressure gauge.
 - 12 Universal coupling plate for skid steer loaders.
- * Hydraulic hoses and connectors to skid steer loader not included.



MEDIA

MOD.		TWX-150
TECHNICAL FEATURES		
Working width (m)		1,50
Total width (m)		1,94
Required pressure range Bar (min-max)		180 - 380
Recommended flow range L/min		140 - 160
Rotor/s cutting diameter (mm)		475
Nr. of hammers	F29 + F37	24 + 2
Counterblades		1 adjustable row
Coupling		Universal coupling plate
Nr. of belts - type		1 PolyChain
Skids		Bolted adjustable (3 positions)
Weight (kg)		1.300
REF. MOD.		HH5J15
OPTIONS		
KM1.F29.5J	Maintenance basic kit (2 hammers F29 + 2 bolts + grease)	
KM2.F29.5J	Maintenance kit (basic kit + 1 belt Poly Chain)	

Hammer F29 Standard



Hammer F37 Standard (sides)

