



TWX



MULCHER

- 1 Body built in high strength steel.
 - 2 2 chain curtains for front protection.
 - 3 Adjustable in height skirts with 3 positions and with deflectors to help the material to enter the chamber.
 - 4 Internal modular replaceable shell in wear resistant steel.
 - 5 Adjustable input counterblade.
 - 6 Rotor with replaceable shafts and with fixed hammers in helical position.
 - 7 Hammers with 2 carbide tips F29 + side scrapers F37.
 - 8 Transmission with 1 reinforced synchronous timing belt.
 - 9 Side extension device between motor and pulleys with ESB system.
 - 10 Hydraulic piston motor Bosch Rexroth with fixed displacement 125 cc.
 - 11 Centralized hydraulic connections, greasing points and visible pressure gauge.
 - 12 Universal coupling plate for skid steer loaders.
- * Hydraulic hoses and connectors to skid steer loader not included.



HARDOX
IN MY BODY

FLEXI
STEEL



ESB



ALE
ALE



HDX
HDX



Ø 200 mm



BELT
SYNCHRO



MEDIA

MOD.	TWX-150
TECHNICAL FEATURES	
Working width (m)	1,50
Total width (m)	1,94
Required pressure range Bar (min-max)	180-380
Recommended flow range L/min	140-160
Rotor/s cutting diameter (mm)	475
Nr. of hammers	F29 + F37
Counterblades	1 adjustable row
Coupling	Universal coupling plate
Nr. of belts - type	1 reinforced synchronous timing belt
Skids	Bolted adjustable (3 positions)
Weight (kg)	1.335
REF. MOD.	HH5J15
OPTIONS	
KM1.F29.5J	Maintenance basic kit (2 hammers F29 + 2 bolts + grease)
KM2.F29.5J	Maintenance kit (basic kit + 1 reinforced synchronous timing belt)

EXCAVATORS

SKIDSTEER LOADERS

PRIME VEHICLES

ANNEX

Hammer F29 Standard



Hammer F37 Standard (sides)

