

TXK

MULCHER

- 1 Body built in high strength steel.
- 2 Protection at front by a quadruple curtain of chains.
- 3 Hydraulic cover with a screen at rear to classify the material and with a built-in leveler.
- 4 Body sides with Sidestep system.
- 5 Adjustable in height skids with 3 positions and with deflectors to help the material to enter into the chamber.
- 6 Rotor with fixed hammers with helical disposition.
- 7 Internal modular replaceable shell in wear resistant steel.
- 8 Adjustable input counterblade.
- 9 Transmission with 6 XPB belts and automatic tensioner.
- 10 Gearbox with built-in free-wheel, input to 540 rpm and 1 3/4" Z6.
- 11 Hammers with 2 carbide tips model F29.
- 12 PTO shaft included with 1 3/8 Z6" tractor side.



HARDOX
IN MY BODY

**FLEXI
STEEL**



ESB



SIDESTEP



ALE



HDX



Ø 200 mm



x6
BELTS



MOD.		TXK-100	TXK-125	TXK-150	TXK-180	
TECHNICAL FEATURES						
Working width (m)		1,00	1,25	1,50	1,80	
Total width (m)		1,40	1,65	1,90	2,20	
Required input power (HP)		70	80	90	100	
Max. allowed power (HP)		130				
Rotor/s cutting diameter (mm)		460				
Gearbox input speed (rpm)		540				
Nr. of hammers	F29	18	22	26	30	
Counterblades		1 adjustable				
Coupling category		Cat. 2				
Nr. of belts - type		6 XPB (automatic tensioner)				
Skids		HARDOX (3 positions)				
Adjustable height control		Skids				
Weight (kg)		980	1.095	1.270	1.526	
REF. MOD.		HM4R10	HM4R12	HM4R15	HM4R18	
OPTIONS						
270	External rear roller					
KM1.F29.4R	Maintenance basic kit (2 hammers F29 + 2 bolts + 2 nuts + grease)					
KM2.F29.4R	Maintenance kit (basic kit + 6 belts XPB)					
OTHERS						
PTO shaft yoke (tractor side)		T1	T2	T3	T4	T5
		1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

Hammer F29 Standard

